



Inductive conductivity meter, ELEMENT Design

- Perfect for concentrated liquids and wide conductivity ranges
- Pre-parameterized variants available for direct start-up
- Measurement device for direct connection to the monitoring level (PLC) via analogue 4...20 mA signal or digital IO-Link or Bürkert system bus (büS)/CANopen communication
- Simulation of process values for diagnostics
- Variants of the sensor available in PP, PVDF or PEEK

Product variants described in the data sheet may differ from the product presentation and description.

Can be combined with

- 

Type S020 ▶
Insertion fitting for flow or analytical measurement
- 

Type 8611 ▶
eCONTROL - Universal controller
- 

Type 8619 ▶
multiCELL - Multi-channel and multi-function transmitter/controller
- 

Type 8693 ▶
Digital electro-pneumatic process controller for integrated mounting on process control valves
- 

Type 8802 ▶
ELEMENT continuous control valve systems - overview

Type description

The Bürkert inductive Type 8228 conductivity meter is used in many industrial processes where measurements are required in aggressive or concentrated media such as acids, alkalis or liquids with high salt contents and a wide measuring range.

This can concern applications like cooling water monitoring (i.e. dilution control), industrial water treatment or the preparation and identification of cleaning liquids, for example in CIP processes.

The device Type 8228 is available in two variants. The first one, the so-called ELEMENT standard is proposed either with two adjustable outputs (one digital and one analogue output) or with four adjustable outputs (two digital and two analogue outputs) and can be equipped with a display. The display is only necessary for start-up, configuration (e.g. measuring range, units, calibration, thresholds) or as a display of process values. The second variant, the so-called ELEMENT neutrino is a device without display, with a digital communication mode that can communicate either in IO-Link or in büS (Bürkert system bus based on CANopen).

Both variants are available with a process connections either via a G 2" union nut for installation into a fitting Type S020 which is connected to the process, or via a clamp 2" according to ASME BPE (clamp 1.5" on request) for CIP applications).

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | validé) printed: 26.03.2024

Table of contents

| | |
|---|-----------|
| 1. General technical data | 4 |
| 1.1. About the device | 4 |
| 1.2. All variants..... | 4 |
| 1.3. ELEMENT standard variant..... | 6 |
| 1.4. ELEMENT neutrino variant..... | 7 |
| 2. Approvals and conformities | 8 |
| 2.1. General notes..... | 8 |
| 2.2. Conformity | 8 |
| 2.3. Standards..... | 8 |
| 2.4. Pressure Equipment Directive (PED)..... | 9 |
| Device used on a pipe | 9 |
| Device used on a vessel | 9 |
| 2.5. North America (USA/Canada) | 9 |
| 2.6. Foods and beverages/Hygiene | 9 |
| 3. Materials | 10 |
| 3.1. Bürkert resistApp | 10 |
| 3.2. Material specifications | 10 |
| ELEMENT standard variant..... | 10 |
| ELEMENT neutrino variant..... | 11 |
| 4. Dimensions | 12 |
| 4.1. ELEMENT standard variant..... | 12 |
| With G 2" process connection | 12 |
| With G 2" process connection, installed in an Insertion fitting Type S020 | 12 |
| With 2" clamp process connection..... | 13 |
| 4.2. ELEMENT neutrino variant..... | 14 |
| With G 2" process connection | 14 |
| With G 2" process connection, installed in an Insertion fitting Type S020 | 14 |
| With 2" clamp process connection..... | 15 |
| 5. Performance specifications | 15 |
| 5.1. Pressure temperature diagram..... | 15 |
| 6. Product installation | 16 |
| 6.1. Installation notes | 16 |
| With G 2" process connection | 16 |
| With 2" clamp process connection..... | 16 |
| 6.2. Mounting options..... | 17 |
| 7. Product operation | 17 |
| 7.1. Measuring principle..... | 17 |
| 7.2. Functional overview | 18 |
| Concentration table..... | 18 |
| 8. Product design and assembly | 19 |
| 8.1. Product assembly | 19 |
| With G 2" process connection | 19 |
| With 2" clamp process connection..... | 19 |
| 9. Product accessories | 20 |

| | |
|--|-----------|
| 10. Networking and combination with other Bürkert products | 20 |
| 10.1. Combination with transmitter/controller and fitting | 20 |
| 10.2. Combination with available Type S020 Insertion fittings DN | 21 |
| 11. Ordering information | 21 |
| 11.1. Bürkert eShop | 21 |
| 11.2. Recommendation regarding product selection..... | 21 |
| With G 2" process connection | 21 |
| With 2" clamp process connection..... | 22 |
| 11.3. Bürkert product filter | 22 |
| 11.4. Ordering chart | 23 |
| ELEMENT standard variant..... | 23 |
| ELEMENT neutrino variant..... | 25 |
| 11.5. Ordering chart accessories..... | 26 |

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | validé) printed: 26.03.2024

1. General technical data

1.1. About the device

The conductivity measurement device consists of a sensor fastened to the transmitter. The device is available in an ELEMENT standard variant or in an ELEMENT neutrino variant.

The process connection of both variants is made via

- a G 2" union nut (for mounting in a Type S020 fitting) for general applications
- a clamp 2" according to ASME BPE (clamp 1.5" on request) for CIP applications.

The ELEMENT standard variant is available with up to two 4...20 mA analogue outputs or with up to two transistor outputs. The ELEMENT neutrino variant is available with digital communication.

The device with digital communication is distinguished by a status indicator on the cover, and is offered with a housing in metal (so-called metallic variant) or in plastic (so-called all-plastic variant for corrosive environmental conditions like in the electronic & semiconductor industry market).

The metallic variant is provided with a digital IO-Link and bÜS (Bürkert system bus, CANopen protocol) communication, the all-plastic variant with a digital IO-Link communication (bÜS available only for service activities such as configuration or calibration).

1.2. All variants

Note:

- The following data applies to all variants mentioned above.
- If the device is mounted in a humid environment or outside, then the maximum voltage allowed is **35 V DC** instead of 36 V DC.

Product properties

Material

Make sure the device materials are compatible with the fluid you are using. Further information can be found in chapter **"3.1. Bürkert resistApp" on page 10.**

Further information on the materials can be found in chapter **"3.2. Material specifications" on page 10.**

Non wetted parts

Union nut Variant for general applications: PC or PPA (with PEEK sensor armature)

Wetted parts

Process connection (clamp) Variant for CIP applications: stainless steel 1.4404 (316L)
 Sensor armature

- Variant for general applications: PP, PVDF or PEEK
- Variant for CIP applications: PEEK (standard) or PVDF (on request)

Compatibility

- Variant for general applications: Any pipe from DN 15...DN 200 which are fitted with Bürkert S020 Insertion fitting. Further information on the available fitting can be found in chapter **"10.1. Combination with transmitter/controller and fitting" on page 20** For the selection of the nominal diameter of the Insertion sensor-fittings, see **data sheet Type S020** ▶.
- Variant for CIP applications: Any pipe from DN 32 which are fitted out with a clamp 2" according to ASME BPE as process connection for the device

Pipe diameter

- Variant for general applications: DN 15...DN 200
- Variant for CIP applications: DN ≥ 32

Dimensions Further information can be found in chapter **"4. Dimensions" on page 12.**

Temperature sensor Integrated in the sensor

Temperature compensation

- None or
- According to a predefined graph (NaCl, NaOH, HNO₃ or H₂SO₄) or
- According to a graph defined especially for your process

Measuring range

Conductivity measurement 100 µS/cm...2 S/cm

Temperature measurement -15...+130 °C (+5...+266 °F)

Concentration

- Conversion of conductivity to dissolved electrolyte concentration (Total dissolved solids (TDS)) by using a user adjustable factor
- Determination of the concentration of certain electrolytes (NaCl, H₂SO₄, HNO₃, NaOH, HCl) as a function of conductivity and temperature

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | validé) printed: 26.03.2024

Performance data

Conductivity measurement

| | |
|----------------------------|--|
| Measurement deviation | ± (2 % of the measured value + 5 µS/cm) |
| Measuring range resolution | 0.1 µS/cm |
| Linearity | ± 2 % |
| Repeatability | ± (0.2 % of the measured value + 2 µS/cm) |
| Response time t_{90} | From 3 s (without filter) to 40 s (with slow filter) |

Temperature measurement

| | |
|------------------------------|------------------------|
| Measurement deviation | ± 1 °C (1.8 °F) |
| Measuring range resolution | 0.1 °C (0.18 °F) |
| 4...20 mA output uncertainty | ± 1 % of current range |

Electrical data

| | |
|---|--|
| Power source (not supplied) | Limited power source according to UL/EN 62368-1 standards or limited energy circuit according to UL/EN 61010-1 paragraph 9.4 |
| Protection against DC polarity reversal | Yes |

Medium data

| | |
|-------------------|--|
| Fluid temperature | <p>With conductivity sensor in:</p> <ul style="list-style-type: none"> • PP: 0...+80 °C (+32...+176 °F) • PVDF: -15...+100 °C (+5...+212 °F) • PEEK: -15...+130 °C (+5...+266 °F) <p>For the variant for general applications, temperature limits may depend on the material the Type S020 Insertion fitting used is made of. Further information can be found in chapter “5.1. Pressure temperature diagram” on page 15, in the data sheet and in the instruction manual, see Type S020 ▶. If the temperature ranges given for the device and the fitting are different, use the most restrictive range.</p> |
| Fluid pressure | <p>With conductivity sensor in:</p> <ul style="list-style-type: none"> • PP: max. PN 6 (87 PSI) • PVDF: max. PN 6 (87 PSI) • PEEK: max. PN 10 (145 PSI) <p>For the variant for general applications, pressure limits may depend on the material the Type S020 Insertion fitting used is made of. Further information can be found in chapter “5.1. Pressure temperature diagram” on page 15, in the data sheet and in the instruction manual, see Type S020 ▶. If the pressure ranges given for the device and the fitting are different, use the most restrictive range.</p> |

Process/Pipe connection & communication

| | |
|--------------------|---|
| Process connection | <ul style="list-style-type: none"> • Variant for general applications: G 2" for use with Type S020 Insertion fitting • Variant for CIP applications: clamp 2" according to ASME BPE (clamp 1.5" on request) |
|--------------------|---|

Approvals and conformities

Directives

| | |
|------------------------------|---|
| CE directive | Further information on the CE directive can be found in chapter “2.3. Standards” on page 8 . |
| Pressure equipment directive | Complying with article 4, paragraph 1 of 2014/68/EU directive Further information on the pressure equipment directive can be found in chapter “2.4. Pressure Equipment Directive (PED)” on page 9 . |
| North America (USA/Canada) | UL Recognized for the USA and Canada |

Environment and installation

| | |
|------------------------|---|
| Ambient temperature | Operating and storage: -10...+60 °C (+14...+140 °F) |
| Relative air humidity | ≤ 85 %, without condensation |
| Height above sea level | Max. 2000 m |
| Operating condition | Continuous |
| Equipment mobility | Fixed |
| Application range | Indoor and outdoor Protect the device against electromagnetic interference, ultraviolet rays and, when installed outdoors, against the effects of climatic conditions. |
| Installation category | Category I according to UL/EN 61010-1 |
| Pollution degree | Degree 2 according to UL/EN 61010-1 |

1.3. ELEMENT standard variant



Product properties

Material

Further information on the materials can be found in chapter [“3.2. Material specifications”](#) on page 10.

Non wetted parts

| | |
|------------------------------|---|
| Cover | Polycarbonate (PC), transparent (opaque on request) |
| Housing | Stainless steel 1.4404 (316L), PPS |
| Screw | Stainless steel 1.4401 (316 (A4)) |
| Grounding terminal and screw | Stainless steel 1.4301 (304 (A2)) |
| Display/configuration module | PC |
| Navigation Key | PBT |
| Seal | EPDM, silicone |
| Fixed connector holder | PPS CF30 |
| Fixed connector | <ul style="list-style-type: none"> Variant for general applications: nickel-plated brass Variant for CIP applications: stainless steel 316L |

Wetted parts

| | |
|------|--|
| Seal | <ul style="list-style-type: none"> Variant for general applications: FKM (standard) or EPDM (option) Variant for CIP applications: EPDM (standard) or FKM (on request) |
|------|--|

Product accessory

| | |
|------------------------------|--|
| Display/configuration module | Grey dot matrix 128 x 64 with backlighting |
|------------------------------|--|

Electrical data

| | |
|---------------------------|--|
| Operating voltage | 12...36 V DC, $\pm 10\%$ oscillation rate, filtered and regulated, Connection to main supply: permanent (through external SELV (Safety Extra Low Voltage) and LPS (Limited Power Source) power supply) |
| Power/Current consumption | <ul style="list-style-type: none"> Without the consumption of the current outputs and the transistor outputs: max. 1 W (25 mA at 12 V DC; inrush current ~100 mA) With the consumption of the current outputs and the transistor outputs: max. 40 W (max. 1 A for the transistor outputs) |
| Output | <p>The device is available with one transistor and one 4...20 mA analogue outputs (2 outputs meter) or with two transistor and two 4...20 mA analogue outputs (4 outputs meter)</p> <ul style="list-style-type: none"> Pulse (transistor): <ul style="list-style-type: none"> – Polarized – Configurable through wiring and through parameterizing as sourcing (PNP) or sinking (NPN) – NPN-output: 1...36 V DC, max. 700 mA (or 500 mA max. per transistor if both transistor outputs are wired) – PNP-output: V+ supply voltage, max. 700 mA (or 500 mA max. per transistor if both transistor outputs are wired) – Galvanic insulation and protected against overvoltage, polarity reversals and short circuit Current (3-wire): <ul style="list-style-type: none"> – 4...20 mA configurable through wiring and through parameterizing as sourcing or sinking, – 22 mA to indicate a fault (can be parametered) – Loop impedance max.: 1100 Ω at 36 V DC; 610 Ω at 24 V DC; 100 Ω at 12 V DC – Response time (10...90 %): 150 ms (default value) |
| Voltage supply cable | <p>The female M12 connector and/or the male M12 connector are not included in the delivery and must be ordered separately, see chapter “11.5. Ordering chart accessories” on page 26.</p> <p>For these connectors, use a shielded cable with:</p> <ul style="list-style-type: none"> diameter: 3...6.5 mm cross section of wires: max. 0.75 mm² |

Process/Pipe connection & communication

| | |
|-----------------------|---|
| Electrical connection | For the device with: <ul style="list-style-type: none"> • 2 outputs meter (3-wire): 1 x 5-pin M12 male connector • 4 outputs meter (3-wire): 1 x 5-pin M12 male + 1 x 5-pin M12 female connectors |
|-----------------------|---|

Approvals and conformities

| | |
|-----------------------------|--|
| Foods and beverages/Hygiene | <ul style="list-style-type: none"> • FDA-FDA declaration of conformity (only for standard or CIP variants with PEEK or PVDF sensor holder and EPDM or FKM seal) • ECR1935/2004 declaration (only for standard or CIP variants with PEEK sensor holder and EPDM seal) |
|-----------------------------|--|

Environment and installation

| | |
|---|--|
| Degree of protection ^{1.)} according to IEC/EN 60529 | IP65, IP67 under the following simultaneous conditions: <ul style="list-style-type: none"> • device wired • cover screwed tight • M12 connector mounted and tightened |
|---|--|

1.) Not evaluated by UL

1.4. ELEMENT neutrino variant



Product properties

Material
 Further information on the materials can be found in chapter **“3.2. Material specifications” on page 10.**

| | |
|-------------------------|--|
| Non wetted parts | |
| Cover | PPS |
| Light guide | Polycarbonat black / PMMA / NBR88 |
| Housing | <ul style="list-style-type: none"> • Stainless steel 1.4404 (316L), PPS (metallic variant) • PPS (all-plastic variant) |
| Grounding terminal | Nickel-plated brass (only metallic variant) |
| Seal | EPDM |
| Fixed connector | <ul style="list-style-type: none"> • Nickel-plated brass (metallic variant) • PA66 (all-plastic variant) |

Electrical data

| | |
|---------------------|--|
| Operating voltage | 12...36 V DC, filtered and regulated Connection to main supply: permanent, through external SELV (Safety Extra Low Voltage) and LPS (Limited Power Source) power supply |
| Current consumption | ≤ 50 mA (with sensor) |
| Power consumption | ≤ 1 W |

| | |
|----------------------|---|
| Input/Output | |
| Digital input/output | Through the communication interface <ul style="list-style-type: none"> • Bürkert system bus (bùS)/CANopen • IO-Link |

| | |
|------------------------------|--|
| Recommended connection cable | The female M12 connector is not included in the delivery and must be ordered separately, see chapter “11.5. Ordering chart accessories” on page 26. For this connector, use according to the variant of the device: <ul style="list-style-type: none"> • a Canopen standard cable for Bürkert system bus (bùS)/CANopen communication, max. 50 m length • a standardised industrial cable (unshielded 3- or 4-wire cable) for IO-Link communication, max. 20 m length |
|------------------------------|--|

Process/Pipe connection & communication

| | |
|-----------------------|--|
| Electrical connection | 1 x 5-pin free positionable M12 male connector |
|-----------------------|--|

Data transfer

| | |
|-----------------------------------|--|
| Digital communication: bùS | |
| External communication | Through bùS (Bürkert system bus, CANopen protocol) |

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | validé) printed: 26.03.2024

Digital communication: IO-Link

| | |
|--------------------------------|--|
| Communication interface | IO-Link device V1.1.2 |
| SIO mode | No |
| Baud rate (data transfer rate) | COM 3 (230.4 kBaud) |
| Type of ports | Class A |
| Cycle time | Min. 5 ms |
| Process data width | 48 Input bits, 8 Output bits |
| IO-Link data storage | Yes |
| Block configuration | No |
| IO device description (IODD) | The device description is available in the operating instructions which can be found on our website under the "User Manuals" heading for Type 8228 ▶. Alternatively, see "Device Description Files" under the "Software" heading for Type 8228 ▶ or at https://ioddfinder.io-link.com |

Environment and installation

| | |
|----------------------|--|
| Degree of protection | <ul style="list-style-type: none"> • IP65^{1.)}, IP67^{1.)} (according to IEC/EN 60529) • NEMA 4X and NEMA 6P (according to NEMA250) (with device installed on the fitting) • UL50E under the following simultaneous conditions: <ul style="list-style-type: none"> • device wired • cover screwed tight • M12 connector mounted and tightened |
|----------------------|--|

1.) Not evaluated by UL

2. Approvals and conformities

2.1. General notes

- The approvals and conformities listed below must be stated when making enquiries. This is the only way to ensure that the product complies with all required specifications.
- Not all available variants of the device can be supplied with the below mentioned approvals or conformities.

2.2. Conformity

In accordance with the Declaration of Conformity, the product is compliant with the EU Directives.

2.3. Standards

The applied standards which are used to demonstrate compliance with the EU Directives are listed in the EU-Type Examination Certificate and/or the EU Declaration of Conformity.

2.4. Pressure Equipment Directive (PED)

The device conforms to article 4, paragraph 1 of the Pressure Equipment Directive (PED) 2014/68/EU under the following conditions:

Device used on a pipe

Note:

- The data in the table is independent of the chemical compatibility of the material and the fluid.
- PS = maximum admissible pressure (in bar), DN = nominal diameter of the pipe

| Type of fluid | Conditions |
|--|-------------------------------------|
| Fluid group 1, article 4, paragraph 1.c.i | DN ≤ 25 |
| Fluid group 2, article 4, paragraph 1.c.i | DN ≤ 32 or PS*DN ≤ 1000 |
| Fluid group 1, article 4, paragraph 1.c.ii | DN ≤ 25 or PS*DN ≤ 2000 |
| Fluid group 2, article 4, paragraph 1.c.ii | DN ≤ 200 or PS ≤ 10 or PS*DN ≤ 5000 |

Device used on a vessel

Note:

- The data in the table is independent of the chemical compatibility of the material and the fluid.
- PS = maximum admissible pressure (in bar), V = vessel volume

| Type of fluid | Conditions |
|--|---|
| Fluid group 1, article 4, paragraph 1.a.i | V > 1 L and PS*V ≤ 25 bar.L or PS ≤ 200 bar |
| Fluid group 2, article 4, paragraph 1.a.i | V > 1 L and PS*V ≤ 50 bar.L or PS ≤ 1000 bar |
| Fluid group 1, article 4, paragraph 1.a.ii | V > 1 L and PS*V ≤ 200 bar.L or PS ≤ 500 bar |
| Fluid group 2, article 4, paragraph 1.a.ii | PS > 10 bar and PS*V ≤ 10000 bar.L or PS ≤ 1000 bar |

2.5. North America (USA/Canada)

| Approval | Description |
|----------|---|
| | <p>Optional: UL Recognized for the USA and Canada The products are UL Recognized for the USA and Canada according to:</p> <ul style="list-style-type: none"> • UL 61010-1 • CAN/CSA-C22.2 No. 61010-1 |


2.6. Foods and beverages/Hygiene

| Conformity | Description |
|------------|---|
| | <p>FDA – Code of Federal Regulations (valid for the variable code PL02, PL03) Only the standard or CIP variants with PEEK or PVDF sensor holder and EPDM or FKM seal are compliant with the Code of Federal Regulations published by the FDA (Food and Drug Administration, USA) according to the manufacturer’s declaration.</p> |
| | <p>EC Regulation 1935/2004 of the European Parliament and of the Council (valid for the variable code PL01, PL02) Only wetted materials of the standard or CIP variants with PEEK sensor holder and EPDM seal are compliant with EC Regulation 1935/2004/EC according to the manufacturer’s declaration.</p> |

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | validé) printed: 26.03.2024

3. Materials

3.1. Bürkert resistApp




Bürkert resistApp – Chemical resistance chart

You want to ensure the reliability and durability of the materials in your individual application case? Verify your combination of media and materials on our website or in our resistApp.

[Start chemical resistance check](#)


3.2. Material specifications

ELEMENT standard variant



With G 2" process connection

| No. | Element | Material |
|-----|-------------------------------------|---------------------------------------|
| 1 | Cover | PC |
| 2 | Seal | Silicone |
| 3 | Housing (top) | PPS |
| 4 | Seals | EPDM |
| 5 | Nut | PC or PPA (with PEEK sensor armature) |
| 6 | Sensor armature | PP, PVDF or PEEK |
| 7 | Seal | FKM (standard) or EPDM (option) |
| 8 | Housing (base) | PPS |
| 9 | Housing (body) | Stainless steel 1.4404 (316L) |
| 10 | Fixed connector holder | PPS CF30 |
| 11 | Grounding terminal and screw | Stainless steel 1.4301 (304 (A2)) |
| 12 | M12 fixed connector (female / male) | Nickel-plated brass |
| 13 | Screws | Stainless steel 1.4401 (316 (A4)) |




With 2" clamp process connection

| No. | Element | Material |
|-----|-------------------------------------|--------------------------------------|
| 1 | Cover | PC |
| 2 | Seal | Silicone |
| 3 | Housing (top) | PPS |
| 4 | Seals | EPDM |
| 5 | Process connection (clamp) | Stainless steel 1.4404 (316L) |
| 6 | Sensor armature | PEEK (standard) or PVDF (on request) |
| 7 | Seal | EPDM (standard) or FKM (on request) |
| 8 | Housing (base) | PPS |
| 9 | Housing (body) | Stainless steel 1.4404 (316L) |
| 10 | Fixed connector holder | PPS CF30 |
| 11 | Grounding terminal and screw | Stainless steel 1.4301 (304 (A2)) |
| 12 | M12 fixed connector (female / male) | Stainless steel 316L |
| 13 | Screws | Stainless steel 1.4401 (316 (A4)) |


DTS 1000220089 EN Version: R Status: RL (released | freigegeben | validé) printed: 26.03.2024

ELEMENT neutrino variant



With G 2" process connection

| No. | Element | Material |
|-----|--------------------------|--|
| 1 | Light guide | PC, PMMA and NBR88 |
| 2 | Cover | PPS |
| 3 | Seal | EPDM |
| 4 | M12 male fixed connector | <ul style="list-style-type: none"> PA66 (all-plastic variant) Nickel-plated brass (metallic variant) |
| 5 | Grounding terminal | Nickel-plated brass (only metallic variant) |
| 6 | Housing (body) | <ul style="list-style-type: none"> PPS (all-plastic variant) Stainless steel 1.4404 (316L), PPS (metallic variant) |
| 7 | Seal | EPDM |
| 8 | Housing (base) | PPS |
| 9 | Union nut | PC or PPA (with PEEK sensor armature) |
| 10 | Seal | FKM (standard) or EPDM (option) |
| 11 | Sensor armature | PP, PVDF or PEEK |



With 2" clamp process connection

| No. | Element | Material |
|-----|----------------------------|--|
| 1 | Light guide | PC, PMMA and NBR88 |
| 2 | Cover | PPS |
| 3 | Seal | EPDM |
| 4 | M12 male fixed connector | <ul style="list-style-type: none"> PA66 (all-plastic variant) Nickel-plated brass (metallic variant) |
| 5 | Grounding terminal | Nickel-plated brass (only metallic variant) |
| 6 | Housing (body) | <ul style="list-style-type: none"> PPS (all-plastic variant) Stainless steel 1.4404 (316L), PPS (metallic variant) |
| 7 | Seal | EPDM |
| 8 | Housing (base) | PPS |
| 9 | Process connection (clamp) | Stainless steel 1.4404 (316L) |
| 10 | Seal | EPDM (standard) or FKM (on request) |
| 11 | Sensor armature | PEEK (standard) or PVDF (on request) |


4. Dimensions

4.1. ELEMENT standard variant

With G 2" process connection

Note:


Dimensions in mm, unless otherwise stated



With G 2" process connection, installed in an Insertion fitting Type S020

Note:

Dimensions in mm, unless otherwise stated



| DN | H | | |
|-----|--------------------|--------------------|--------------|
| | T-Fitting | Plastic spigot | Metal spigot |
| 15 | 235 ^{1.)} | – | – |
| 20 | 235 ^{1.)} | – | – |
| 25 | 235 ^{1.)} | – | – |
| 32 | 235 | – | – |
| 40 | 239 | – | – |
| 50 | 245 | – | 240 |
| 65 | 245 | 266 ^{2.)} | 246 |
| 80 | – | 266 ^{2.)} | 251 |
| 100 | – | 266 ^{2.)} | 261 |
| 125 | – | 301 | 272 |
| 150 | – | 308 | 283 |
| 200 | – | 329 | 304 |


1.) Only use plastic fittings with true union process connection in analytical variant, with nut and solvent/fusion socket according to DIN 8063 (PVC), to DIN 16962 (PP) or to ISO 10931 (PVDF).

2.) Using fusion spigot (Article no. 418652, 418660 or 418644 in PP, PVDF or PE) for orifice DN 65...DN 100

With 2" clamp process connection

Note:

- Dimensions in mm, unless otherwise stated
- Technical data for 1.5" clamp available on request




4.2. ELEMENT neutrino variant

With G 2" process connection

Note:


Dimensions in mm, unless otherwise stated



With G 2" process connection, installed in an Insertion fitting Type S020

Note:

Dimensions in mm, unless otherwise stated



| DN | H | | |
|-----|--------------------|--------------------|--------------|
| | T-Fitting | Plastic spigot | Metal spigot |
| 15 | 178 ^{1.)} | – | – |
| 20 | 178 ^{1.)} | – | – |
| 25 | 178 ^{1.)} | – | – |
| 32 | 178 | – | – |
| 40 | 182 | – | – |
| 50 | 188 | – | 183 |
| 65 | 188 | 209 ^{2.)} | 189 |
| 80 | – | 209 ^{2.)} | 194 |
| 100 | – | 209 ^{2.)} | 204 |
| 125 | – | 244 | 215 |
| 150 | – | 251 | 226 |
| 200 | – | 272 | 247 |


1.) Only use plastic fittings with true union process connection in analytical variant, with nut and solvent/fusion socket according to DIN 8063 (PVC), to DIN 16962 (PP) or to ISO 10931 (PVDF).

2.) Using fusion spigot (Article no. 418652, 418660 or 418644 in PP, PVDF or PE) for orifice DN 65...DN 100

With 2" clamp process connection


Note:

- Dimensions in mm, unless otherwise stated
- Technical data for 1.5" clamp available on request



5. Performance specifications

5.1. Pressure temperature diagram



6. Product installation

6.1. Installation notes


With G 2" process connection

Note:


The conductivity meter Type 8228 can be installed into most of Bürkert Insertion fittings Type S020.

Further information on the combination possibilities of the fittings can be found in chapter **"10.2. Combination with available Type S020 Insertion fittings DN"** on page 21.

See **data sheet Type S020** ▶ for more information.

| Installation example | Description |
|---|--|
|  | <p>The 8228 conductivity meter (standard or neutrino variant) is installed in the pipe together with a Bürkert insertion fitting (Type S020). Select and install the required fitting onto the pipe, according to specific requirements of the sensor and fitting material, temperature and pressure. Then cautiously install the unit on the fitting and tighten with the nut.</p> <p>Further information on the assembly can be found in chapter "8.1. Product assembly" on page 19.</p> |


With 2" clamp process connection

| Installation example | Installation example |
|---|---|
|  | <p>Mount the device (standard or neutrino variant) in a stainless steel pipe of min. DN 32 which is fitted out with a clamp 2" according to ASME BPE as process connection for the device and carefully positioning it as shown opposite. The electrical connections have to be parallel with the pipe.</p> |

6.2. Mounting options

Note:

- In order to get a reliable measurement, air bubbles must be avoided and the mounting location must ensure that the electrode is continuously and completely immersed in the flow stream.
- The device must be protected from heat, direct sunlight and other environmental influences.
- The sensor can be installed in any position.
- The drawings show the assembly of the measuring device in the standard ELEMENT variant with a G 2" process connection. This also applies to the other variants.



7. Product operation

7.1. Measuring principle

Conductivity is defined by the property of a solution to conduct electrical current. The charge carriers are ions (e.g. dissolved salts or acids).

The measuring cell consists of an emitting coil and a receiving coil, which are placed around the hollow measuring tube. This assembly is inserted into the lower part of the moulded probe housing and is thus separated from the fluid surrounding the probe, but which is also present in the hole crossing the probe (hollow measuring tube).

An alternating voltage (AC) is applied to the primary (emitting) coil, which generates a magnetic field. Following Lenz-Faraday's law, an electric current is then induced in the fluid, which then generates a magnetic field that is detected by the secondary (receiver) coil. The intensity of the current measured at the secondary coil is a direct function of the quantity of ions in the solution, and the conductivity is derived.

The electrical conductivity of a given medium also depends on its temperature. Several temperature compensation modes are available and can be chosen to satisfy the needs for the different applications. The integrated transmitter module converts the measured signals (conductivity and temperature) into common values, monitors limit values, displays different values in different physical units via the optional display module (if mounted) and computes the output signals.

Depending on the variant, the device Type 8228 is available with either:

- one transistor and one 4...20 mA analogue outputs (1 x M12) or
- two transistor and two 4...20 mA analogue outputs (2 x M12).

The 4...20 mA standard output signal is proportional to the conductivity and/or to the temperature of the fluid. The conductivity meter is a three-wire device and requires a power supply of 12...36 V DC.


The ELEMENT neutrino device provides in a digital way different measures (conductivity, temperature, resistivity, and concentration) that can be accessed by the IO-Link or the bus terminal.

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | valide) printed: 26.03.2024

7.2. Functional overview

Concentration table

Both variant of the transmitter Type 8228 transmitter are able to determine the concentration of a two-component mixture based on its conductivity and temperature. For this purpose, a concentration table for five different aqueous solutions is available. One of nine concentration ranges, which are perfectly matched to the application, can be selected.



Note: the "%" involved on the x-axis refers to "% mass".

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | valide) printed: 26.03.2024

8. Product design and assembly

8.1. Product assembly

The conductivity meter Type 8228 (standard or neutrino variant) consists of an inductive sensor, plugged-in and pinned to an enclosure with cover, containing the electronic module. The measuring element consists of a pair of magnetic coils (called primary and secondary) moulded in a PP, PVDF or PEEK armature. A temperature probe (without direct contact to the fluid) is fitted to the sensor armature for automatic temperature compensation (standard feature).


A removable display/configuration module complements the ELEMENT standard transmitter variant. The ELEMENT standard conductivity meter can operate independently of the display but it will be required for parameterize the device (i.e. selection of sensor cell constant, language, measuring range, engineering units, calibration...) and also for visualizing continuously the measured and processed data. The ELEMENT neutrino conductivity meter is parameterize and communicates via a digital IO-Link or bûS (Bürkert system bus, CANopen protocol) interface.

With G 2" process connection


Note:

The Bürkert Type S020 Insertion fitting ensures simple installation into pipelines from DN 15...DN 200.

See **data sheet Type S020** ▶ for more information.



With 2" clamp process connection





DTS 1000220089 EN Version: R Status: RL (released | freigegeben | validé) printed: 26.03.2024

9. Product accessories

Note:

To configure a device with a digital communication, use the USB-büS interface Type 8923 and the Bürkert Communicator software Type 8920.





See **Software manual Type 8920** ▶ for more information.

| Accessories | No. | Description |
|--|-----|--|
| USB-büS interface set 1  | 1 | Quick-Start |
| | 2 | Power supply: 100...240 V AC/ 24 V DC 1 A and adaptors for power supply worldwide use |
| | 3 | büS terminating resistor on büS Y-splitter |
| | 4 | 5-pin M12 male connector wired on free end cable, cable length: 0.2 m |
| | 5 | büS connection cable with 5-pin M12 male connector, micro USB B plug, cable length: 0.3 m |
| | 6 | büS adaptor with 5-pin M12 male connector, A-coded to 5-pin M12 male connector, A-coded |
| | 7 | büS stick (USB to büS/CANopen adaptor) |
| | 8 | büS service cable with 5-pin M12 female connector, mini USB plug and circular female connector for power supply, cable length: 0.7 m |
| | 9 | Magnetic key |
| | 10 | CD - Communicator (30-day license without registration, update and licensing over Bürkert home page) |
| USB-büS interface set 2  | 5 | |
| | 7 | |
| | 8 | |

10. Networking and combination with other Bürkert products

10.1. Combination with transmitter/controller and fitting

Example:


| | | | |
|---|---|--|---|
|  <p>Type 8228</p> | All variants | | Variant with G 2" process connection |
| |  <p>Type 8619 ▶ multiCELL Transmitter/ Controller</p> |  <p>Type 8611 ▶ eCONTROL - Universal controller panel, wall or rail-mounting variant</p> |  <p>Type 8802 ▶ (2301 & 8693) ELEMENT Continuous control valve systems</p> |

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | valide) printed: 26.03.2024

10.2. Combination with available Type S020 Insertion fittings DN

Note:

Only for device with G 2" process connection




Note A: Only use plastic fitting in analytical variant with true union according to DIN 8063 (PVC), DIN 16962 (PP) or ISO 10931 (PVDF).

See **data sheet Type S020** ▶ for more information.

11. Ordering information

11.1. Bürkert eShop



Bürkert eShop – Easy ordering and quick delivery

You want to find your desired Bürkert product or spare part quickly and order directly? Our online shop is available for you 24/7. Sign up and enjoy all the benefits.

[Order online now](#)

11.2. Recommendation regarding product selection

With G 2" process connection

Note:

When only ordering devices without a display/configuration module, make sure that you have a display/configuration module at least for parameterising the device. Otherwise you must also order one (see chapter **“11.5. Ordering chart accessories” on page 26**) or order a pre-configured device (see chapter **“11.4. Ordering chart” on page 23**).

A complete conductivity measurement equipment consists of a ELEMENT conductivity meter (standard or neutrino variant) Type 8228, a removable display/configuration module (only for ELEMENT standard variant) and a Bürkert Insertion fitting Type S020.

See **data sheet Type S020** ▶ for more information.

Two or three different components must be ordered in order to select a complete device. The following information is required:

- **Article no.** of the desired conductivity sensor **Type 8228** available with or without display/configuration module (see chapter **“11.4. Ordering chart” on page 23**)
- **Article no.** of the removable display/configuration module, if necessary (see chapter **“11.5. Ordering chart accessories” on page 26**).
- **Article no.** of the selected Insertion fitting **Type S020** (DN 15...DN 200)

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | valide) printed: 26.03.2024

With 2" clamp process connection

Note:

When only ordering devices without a display/configuration module, make sure that you have a display/configuration module at least for parameterising the device. Otherwise you must also order one (see chapter “11.5. Ordering chart accessories” on page 26).

A complete conductivity measurement equipment consists of a ELEMENT conductivity meter (standard or neutrino variant), a removable display/configuration module (only for ELEMENT standard variant).

One or two different components must be ordered in order to select a complete device. The following information is required:

- **Article no.** of the desired conductivity sensor **Type 8228** available with or without display/configuration module (see chapter “11.4. Ordering chart” on page 23)
- **Article no.** of the removable display/configuration module, if necessary (see chapter “11.5. Ordering chart accessories” on page 26).

11.3. Bürkert product filter



Bürkert product filter – Get quickly to the right product

You want to select products comfortably based on your technical requirements? Use the Bürkert product filter and find suitable articles for your application quickly and easily.

[Try out our product filter](#)

11.4. Ordering chart

ELEMENT standard variant

Conductivity meter to be configured

Note:

- All settings as well as the digital output have to be configured with the display/configuration module (must be ordered separately).
- The following article nos. have a transparent cover as standard.

| Operating voltage | Output | Material | | UL approval | Electrical connection | Article no. | |
|---|---|---------------------|--|--|--------------------------|-----------------|--------------|
| | | Sensor armature | Sensor seal | | | Without display | With display |
| With G 2" process connection, for general applications | | | | | | | |
| 12...36 V DC | 1 x transistor NPN/PNP + 1 x 4...20 mA | PP | FKM ^{1.)} | – | 5-pin M12 male connector | 565601 | 566601 |
| | | | | UL Recognized | | 565611 | 566611 |
| | | PVDF | – | 565603 | | 566603 | |
| | | | UL Recognized | 565613 | | 566613 | |
| | | PEEK ^{2.)} | – | 565605 | | 566605 | |
| | | | UL Recognized | 565615 | | 566615 | |
| | 2 x transistors NPN/PNP + 2 x 4...20 mA | PP | – | 5-pin M12 male and 5-pin M12 female connectors | – | 565602 | 566602 |
| | | | | | UL Recognized | 565612 | 566612 |
| | | PVDF | – | | 565604 | 566604 | |
| | | | UL Recognized | | 565614 | 566614 | |
| | | PEEK ^{2.)} | – | | 565606 | 566606 | |
| | | | UL Recognized | | 565616 | 566616 | |
| With 2" clamp process connection according to ASME BPE, for CIP applications | | | | | | | |
| 12...36 V DC | 1 x transistor NPN/PNP + 1 x 4...20 mA | PEEK | EPDM ^{3.)} | – | 5-pin M12 male connector | 567200 | 567478 |
| | | | | UL Recognized | | 567480 | 567482 |
| | 2 x transistors NPN/PNP + 2 x 4...20 mA | – | 5-pin M12 male and 5-pin M12 female connectors | – | 567199 | 567479 | |
| | | | | UL Recognized | 567481 | 567483 | |

1.) The following is supplied with every device: FKM seal as standard (already mounted), 1 set with a green FKM seal and a black EPDM seal for the sensor.
 2.) Union nut in PPA
 3.) FKM is available on request

| Further variants on request | |
|-----------------------------|--|
| | <p>Material</p> <ul style="list-style-type: none"> • For variant with G 2" process connection: All-plastic housing and M12 plastic connectors • For variant with clamp process connection PVDF sensor armature FKM seal |
| | <p>Process connection</p> <p>Clamp 1½"</p> |

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | validé) printed: 26.03.2024

Conductivity meter pre-configured for direct start-up

Note:

- The installation expense is reduced as the device can be directly started up.
- Default setting: without filtering, temperature compensation linear 2 %/°C, 1 analogue output in sink mode and 1 digital output (transistor: not assigned)
- The following article nos. have an opaque cover as standard.

| Operating voltage | Conductivity range (4...20 mA output corresponds to ...) | Material | | UL approval | Electrical connection | Article no. |
|---|--|---------------------|--------------------|-------------|--------------------------|-----------------|
| | | Sensor armature | Sensor seal | | | Without display |
| With G 2" process connection, for general applications | | | | | | |
| 12...36 V DC | 0...1 mS/cm | PP | FKM ^{1.)} | - | 5-pin M12 male connector | 566560 |
| | 0...10 mS/cm | | | | | 566561 |
| | 0...100 mS/cm | | | | | 566562 |
| | 0...1 S/cm | | | | | 566563 |
| | 0...1 mS/cm | PVDF | 566564 | | | |
| | 0...10 mS/cm | | 566565 | | | |
| | 0...100 mS/cm | | 566566 | | | |
| | 0...1 S/cm | | 566567 | | | |
| | 0...1 mS/cm | PEEK ^{2.)} | 566568 | | | |
| | 0...10 mS/cm | | 566569 | | | |
| | 0...100 mS/cm | | 566570 | | | |
| | 0...1 S/cm | | 566571 | | | |

1.) The following is supplied with every device: FKM seal as standard (already mounted), 1 set with a green FKM seal and a black EPDM seal for the sensor.
 2.) Union nut in PPA

| Further variants on request | |
|---|---|
| <p>Material For variant with G 2" process connection: All-plastic housing and M12 plastic connectors</p> | <p>Process connection Clamp 1½", 2"</p> |
| <p>Additional Configurations: 2- or 4- outputs, filter, temperature compensation, threshold, etc.</p> | |

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | validé) printed: 26.03.2024

ELEMENT neutrino variant



Note:

The communication protocol is selected automatically by the device depending on the master controlling it.

| Operating voltage | Output | Material | | UL approval | Electrical connection | Article no. |
|---|---|---------------------|---------------------|---------------|--------------------------|-------------|
| | | Sensor armature | Sensor seal | | | |
| Metallic variant with G 2" process connection, for general applications | | | | | | |
| 12...36 V DC | Digital IO-Link and būs/ CANopen communication | PP | FKM ^{1.)} | - | 5-pin M12 male connector | 574278 |
| | | | | UL Recognized | | 574279 |
| | | PVDF | | - | | 574290 |
| | | | | UL Recognized | | 574291 |
| | | PEEK ^{2.)} | | - | | 574280 |
| | | | | UL Recognized | | 574281 |
| Metallic variant 2" with clamp process connection according to ASME BPE, for CIP applications | | | | | | |
| 12...36 V DC | Digital IO-Link and būs/ CANopen communication | PEEK | EPDM ^{3.)} | - | 5-pin M12 male connector | 574282 |
| | | | | UL Recognized | | 574283 |
| All-plastic variant with G 2" process connection, for general applications | | | | | | |
| 12...36 V DC | Digital IO-Link communica- tion | PP | FKM ^{1.)} | - | 5-pin M12 male connector | 574284 |
| | | | | UL Recognized | | 574285 |
| | | PVDF | | - | | 574288 |
| | | | | UL Recognized | | 574289 |
| | | PEEK ^{2.)} | | - | | 574286 |
| | | | | UL Recognized | | 574287 |






























1.) FKM seal in standard; 1 set including a green FKM and a black EPDM seals for the sensor is supplied with each measuring device.






















2.) Union nut in PPA

| Further variants on request | |
|--|--|
|  <p>Material</p> <ul style="list-style-type: none"> For variant with G 2" process connection: All-plastic housing and M12 plastic connectors For variant with clamp process connection PVDF sensor armature FKM seal |  <p>Process connection Clamp 1½"</p> |

DTS 1000220089 EN Version: R Status: RL (released | freigegeben | validé) printed: 26.03.2024

11.5. Ordering chart accessories

| Description | Article no. |
|---|--|
| Seals | |
| For ELEMENT neutrino variant | |
| EPDM seal for cover/housing sealing | 561752  |
| Spare part | |
| For ELEMENT standard variant | |
| Opaque cover with seal (1 screw cover with EPDM seal + 1 quarter turn closing cover with silicone seal) | 560948  |
| Transparent cover with seal (1 screw cover with EPDM seal + 1 quarter turn closing cover with silicone seal) | 561843  |
| Mounting accessory | |
| For ELEMENT standard and neutrino variants with G 2" process connection, for general applications | |
| Set with a green FKM seal and a black EPDM seal | 552111  |
| Fastening ring (open) for Type S020 Insertion fitting | 619205  |
| PC union nut for Type S020 Insertion fitting | 619204  |
| Electrical connection | |
| For all variants | |
| M12 female connector with plastic threaded clamping ring, 5-pin, straight, to be wired | 917116  |
| M12 female connector with moulded cable (shielded), 5-pin, straight, cable length: 2 m | 438680  |
| For ELEMENT standard variant | |
| M12 male connector with plastic threaded clamping ring, 5-pin, straight, to be wired | 560946  |
| M12 male connector with moulded cable (shielded), 5-pin, straight, cable length: 2 m | 559177  |
| Configuration accessory | |
| For ELEMENT standard variant | |
| Removable display/configuration module (with instruction sheet) | 559168  |
| For all variants | |
| Buffer solution, 300 ml, conductivity standard: 706 µS/cm, ±2 % accuracy | 440018  |
| Buffer solution, 300 ml, conductivity standard: 1413 µS/cm, ±1 % accuracy | 440019  |
| Buffer solution, 300 ml, conductivity standard: 100 mS/cm, ±1 % accuracy | 440020  |
| System Connect | |
| Type ME43 Gateway/Interface | |
| Industrial Ethernet gateway (PROFINET IO, EtherNet/IP, Modbus TCP, EtherCAT®) | 307390  |
| PROFIBUS gateway (PROFIBUS DPV1) | 307393  |
| Type ME61 Display | |
| FieldConnect ME61 3.5" display (8.9 cm) | 368544  |
| EDIP Accessories | |
| büS Stick Set | |
|  USB-büS interface set 1 (Type 8923) Further information can be found in chapter "9. Product accessories" on page 20. | 772426  |
| USB-büS interface set 2 (Type 8923) Further information can be found in chapter "9. Product accessories" on page 20. | 772551  |
| Connectors | |
| büS M12 female connector, 5-pin, straight, A-coded | 772416  |
| büS M12 male connector, 5-pin, straight, A-coded | 772417  |
| büS M12 female connector, 5-pin, angled, A-coded | 772418  |
| büS M12 male connector, 5-pin, angled, A-coded | 772419  |
| büS Y-distributor (M12 female connector, 5-pin to M12 male and female connectors, 5-pin) | 772420  |
| büS Y-distributor with power interrupt (M12 female connector, 5-pin to M12 male and female connectors, 5-pin) | 772421  |
| büS adaptor (M12 male connector, 5-pin, A-coded to M12 male connector, 5-pin, A-coded) | 772867  |
| büS terminating resistor 120 ohms, M12 male connector, 5-pin | 772424  |
| büS terminating resistor 120 ohms, M12 female connector, 5-pin | 772425  |

| Description | | Article no. |
|---|-------|--|
| Connectors with cable | | |
| Adaptor cable with M12 female connector, 8-pin to M12 male connector, 5-pin | 0.5 m | 773286  |
| M12 female connector, 5-pin, angled, moulded on büS cable, with open leads | 0.7 m | 772626  |
| M12 female connector, 5-pin, straight, moulded on büS cable, with open leads | 1 m | 772409  |
| | 3 m | 772410  |
| | 5 m | 772411  |
| | 10 m | 772412  |
| M12 male connector, 5-pin straight and micro USB connector, moulded on büS cable | 0.3 m | 773254  |
| M12 female connector, 8-pin, straight, moulded on büS cable, with open leads | 2 m | 919061  |
| Extensions | | |
|  M12 female and male connectors, 5-pin, straight, moulded on büS cable, shielded | 0.1 m | 772492  |
| | 0.2 m | 772402  |
| | 0.5 m | 772403  |
| | 1 m | 772404  |
| | 3 m | 772405  |
| | 5 m | 772406  |
| | 10 m | 772407  |
| | 20 m | 772408  |
| Power supply unit for standard rail Type 1573 | | |
| 100...240 V AC / 24 V DC, 1 A (Class 2 according to NEC) | | 772361  |
| 100...240 V AC / 24 V DC, 2 A (Class 2 according to NEC) | | 772362  |
| 100...240 V AC / 24 V DC, 3.8 A (Class 2 according to NEC) | | 772898  |
| 100...240 V AC / 24 V DC, 10 A | | 772698  |